

- Education
- Healthcare
- Hotels
- Leisure
- Office
- Retail




Description

Accessible acoustical ceiling system with pin perforated panels.

Features and Benefits

- Product performance tested according to EN 13964
- Mid range sound absorption, provides balance to room acoustics
- Mid range sound attenuation, ideal for general commercial construction
- Maximum economy and design simplicity
- Easy to trim and install
- Ideal with DONN® DX® Suspension Systems (for more information see reverse side)

DONN® Grid Options



Pattern	Edge	Size (mm)	Item No.	Acoustical performance			LR	Colour	Grid option
				NRC	α_W	DncW			
Athena HP	SQ	600 x 600 x 14	DA2122M	0,60	0,60	31 dB	≥ 85%	White	A,B1,D
Athena HP	SQ	1200 x 600 x 14	DA2222M	0,60	0,60	31 dB	≥ 85%	White	A,B1,D

Sound Absorption	Hz	125	250	500	1000	2000	4000
	α_S	0,41	0,44	0,50	0,69	0,69	0,56

Composition

Contains recycled material, no asbestos. Tile is a wet felted blend of cellulose fibres, NC mineral fibre, perlite, organic binders and inorganic fillers. Pre-finished with primer and top coat paints.

Fire reaction

A2 - s1, d0 (EN 13964)

Humidity resistance

Maximum 90% RH/30°C
Class B (EN 13964)

Thermal resistance

$\lambda = 0,057 \text{ W/(m}\cdot\text{k)}$

Weight

ca. 4,0 kg/m²

Maintenance

Easily cleaned using soft brush, vacuum or damp sponge.

Specifications

Create full system specifications on-line. Copy and paste to your documents. View www.usg.com/europe.

USG Deutschland GmbH

Metalstraße 1
41751 Viersen
Deutschland

Tel: +49 (0)2162 95 70
Fax: +49 (0)2162 44 61
e-mail: Info-de@usg.com