



Description


Accessible acoustical ceiling system with fine non-directional fissured, perforated pattern.

Features and Benefits

- Product performance tested according to EN 13964
- 360° non directional pattern with a fresh, young appearance offers fast, economical installation
- Mid range sound absorption, ideal for general commercial constructions
- Provides balance to room acoustics
- Easy to trim and install
- Excellent price-value-ratio and maximum economy
- Ideal with DONN® DX® Suspension Systems (for more information see reverse side)

- Education
- Hotels
- Healthcare
- Leisure
- Office
- Retail

DONN® Grid Options



Pattern	Edge	Size (mm)	Item No.	Acoustical performance			LR	Colour	Grid option
				NRC	α_w	DncW			
Europa XII	SQ	600 x 600 x 12	DA12119M	0,60	0,60	29dB	≥85%	White	A,B1,D

Sound Absorption	Hz	125	250	500	1000	2000	4000
	α_s	0,38	0,48	0,52	0,63	0,77	0,66

Composition

Contains recycled material, no asbestos. Tile is a wet felted blend of cellulose fibres, NC Mineral fibres, perlite, organic binders and top coat paints. Pre-finished with primer and top coat paints.

Fire reaction

B - s1, d0 (EN 13964)

Humidity resistance

Maximum 70% RH/25°C
Class A (EN 13964)

Thermal resistance

$\lambda = 0,057 \text{ W/(m·k)}$

Weight

ca. 2,8 kg/m²

Maintenance

Easily cleaned using soft brush or vacuum.

Specifications

Create full system specifications on-line. Copy and paste to your documents. View www.usg.com/europe.

USG Deutschland GmbH

Metalstraße 1
41751 Viersen
Deutschland

Tel: +49 (0)2162 95 70
Fax: +49 (0)2162 44 61
E-Mail: info-de@usg.com